

Attorney Docket No. FILM.P008

IN THE CLAIMS

1 1. (Currently amended) A substrate imaging system, comprising:
2 a carrier holding a substrate;
3 a platen holding a polishing pad;
4 a frame for disposing the platen relative to the carrier; and
5 an reflectance image processing subsystem for acquiring one or more two-
6 dimensional images of the substrate during CMP of the substrate and deriving therefrom
7 from the images information about the substrate useful for subsequent CMP of the
8 substrate, wherein the images comprise an optical representation of at least a portion of
9 the substrate.

1 2. (Previously presented) The system of claim 1 further comprising a
2 rotational device for rotating the platen.

1 3. (Previously presented) The system of claim 1 wherein the reflectance
2 image processing subsystem further comprises a capturing device for capturing a
3 plurality of one-dimensional reflectance images and deriving the one or more two-
4 dimensional images therefrom.

1 4. (Original) The system of claim 1 wherein the substrate further comprises a
2 pad-contacting surface.

1 5. (Previously presented) The system of claim 4 wherein the reflectance
2 image processing subsystem further comprises a capturing device for capturing a
3 plurality of one-dimensional images from light reflected from the pad-contacting surface,
4 and deriving the one or more two-dimensional images therefrom.

1 6. (Original) The system of claim 1 wherein the one or more two-dimensional
2 images comprise spectral images.

Attorney Docket No. FILM.P008

1 7. (Original) The system of claim 1 wherein the one or more two-dimensional
2 images are derived from data points.

1 8. (Original) The system of claim 7 wherein the data points are substantially
2 contiguous.

1 9. (Original) The system of claim 7 wherein the data points are substantially
2 non-contiguous.

1 10. (Currently amended) A substrate imaging system comprising:
2 a carrier holding a substrate, the substrate having a pad-contacting surface;
3 a platen holding a polishing pad;
4 a frame for operatively disposing the platen relative to the carrier; and
5 an image processing subsystem for capturing, from light reflected from the pad-
6 contacting surface and transmitted through one or more optically transparent elements in
7 the platen and/or polishing pad, a plurality of one-dimensional images representative of at
8 least a portion of the pad-contacting surface of the substrate during traversal of the
9 opening and/or optically transparent elements, and deriving ~~therefrom~~ from the images a
10 frame comprising frame data providing information about the substrate useful for
11 subsequent chemical-mechanical processing of the substrate, wherein the images
12 comprise an optical representation of at least a portion of the substrate.

1 11. (Previously presented) The system of claim 10 further comprising a
2 rotational device for rotating the platen.

1 12. (Original) The system of claim 10 wherein the one-dimensional images
2 comprise line images.

1 13. (Original) The system of claim 10 wherein the image processing subsystem
2 comprises a light source, a first bundle of optical fibers carrying light from the light
3 source to the slit in the platen, and a second bundle of optical fibers carrying light

Attorney Docket No. FILM.P008

4 reflected from the pad-contacting surface to a wavelength dispersive element for
5 dissecting spatial components of the one-dimensional images into their respective
6 wavelength components.

1 14. (Original) The system of claim 13 wherein the image processing subsystem
2 further comprises a two-dimensional imager having a spatial dimension and a spectral
3 dimension for receiving the dissected light from the wavelength dispersive element, and
4 providing a two-dimensional collection of data for each of the one-dimensional images, a
5 first dimension of the collection comprising a spatial dimension, and a second dimension
6 of the collection comprising a spectral dimension, and a processor for deriving a frame
7 from a plurality of the two-dimensional collections.

1 15. (Original) The system of claim 13 wherein the optical fibers in the first and
2 second bundles each have terminating ends arranged in a fiber assembly element fitted to
3 an underside of the platen.

1 16. (Original) The system of claim 15 wherein the terminating ends of the fibers
2 are arranged in an arrangement in which terminating ends of fibers in the first bundle
3 form first and second rows, and the terminating ends of fibers in the second bundle form
4 a third row placed between the first and second rows.

1 17. (Currently amended) A whole-substrate imaging system comprising:
2 a carrier holding a substrate, the substrate having a pad-contacting surface with a
3 maximum planar dimension;
4 a platen having a radius and holding a polishing pad, the platen including a slit
5 having a length equal to or exceeding the maximum planar dimension of the substrate,
6 the length disposed substantially along the platen radius, and the polishing pad having an
7 optically transparent element located at about the slit;
8 a frame for operatively disposing the platen relative to the carrier, such that the
9 pad-contacting surface of the substrate contacts the polishing pad, and substantially

Attorney Docket No. FILM.P008

10 completely traverses the slit when the pad-contacting surface moves relative to the platen;
11 and
12 an image processing subsystem for capturing, from light reflected from the pad-
13 contacting surface and transmitted through the optically transparent element and the slit,
14 a plurality of one-dimensional images representative of the substantial entirety of the pad-
15 contacting surface of the substrate during traversal of the pad-contacting surface past the
16 slit, and deriving ~~therefrom~~ from the images a frame comprising frame data useful for
17 subsequent chemical-mechanical processing of the substrate, wherein the images
18 comprise an optical representation of one or more portions of the substrate.

1 18. (Previously presented) The system of claim 17 further comprising a
2 rotational device for rotating the platen.

1 19. (Original) The system of claim 17 wherein the one-dimensional images
2 comprise line images.

1 20. (Original) The system of claim 17 wherein the image processing subsystem
2 comprises a light source, a first bundle of optical fibers carrying light from the light
3 source to the slit in the platen, and a second bundle of optical fibers carrying light
4 reflected from the pad-contacting surface to a wavelength dispersive element for
5 dissecting spatial components of the one-dimensional images into their respective
6 wavelength components.

1 21. (Original) The system of claim 20 wherein the image processing subsystem
2 further comprises a two-dimensional imager having a spatial dimension and a spectral
3 dimension for receiving dissected light from the wavelength dispersive element, and
4 providing a two-dimensional collection of data for each of the one-dimensional images, a
5 first dimension of the collection comprising a spatial dimension, and a second dimension
6 of the collection comprising a spectral dimension, and a processor for deriving a frame
7 from a plurality of two-dimensional collections.

Attorney Docket No. FILM.P008

1 22. (Original) The system of claim 20 wherein the optical fibers in the first and
2 second bundles each have terminating ends arranged in a fiber assembly element fitted to
3 an underside of the platen.

1 23. (Original) The system of claim 22 wherein the terminating ends of the fibers
2 are arranged in an arrangement in which terminating ends of fibers in the first bundle
3 form first and second rows, and the terminating ends of fibers in the second bundle form
4 a third row placed between the first and second rows.

1 24. (Withdrawn) A whole-die imaging system comprising:
2 a carrier holding a substrate, the substrate having a pad-contacting surface
3 forming a die and having a maximum planar dimension;
4 a rotating platen having a radius and holding a polishing pad, the platen including
5 a slit having a length approximately equal to the maximum planar dimension of the die,
6 the length disposed substantially along the platen radius, and the polishing pad having an
7 optically transparent element located at about the slit;
8 a frame for operatively disposing the rotating platen relative to the carrier, such
9 that the pad-contacting surface of the substrate contacts the polishing pad, and
10 substantially completely traverses the slit within a rotation of the platen; and
11 an image processing subsystem for capturing, from light reflected from the pad-
12 contacting surface and transmitted through the optically transparent element and the slit,
13 a plurality of one-dimensional images representative of the substantial entirety of the pad-
14 contacting surface of the die during traversal of the pad-contacting surface past the slit,
15 and deriving therefrom a frame comprising frame data providing information about the
16 die useful for subsequent chemical-mechanical processing of the substrate.

1 25. (Withdrawn) The system of claim 24 wherein the one-dimensional images
2 comprise line images.

1 26. (Withdrawn) The system of claim 24 wherein the image processing subsystem
2 comprises a light source, a first bundle of optical fibers carrying light from the light

Attorney Docket No. FILM.P008

3 source to the slit in the platen, and a second bundle of optical fibers carrying light
4 reflected from the pad-contacting surface to a wavelength dispersive element for
5 dissecting spatial components of the one-dimensional images into their respective
6 wavelength components.

1 27. (Withdrawn) The system of claim 26 wherein the image processing subsystem
2 further comprises a two-dimensional imager having a spatial dimension and a spectral
3 dimension for receiving dissected light from the wavelength dispersive element, and
4 providing a two-dimensional collection of data for each of the one-dimensional images, a
5 first dimension of the collection comprising a spatial dimension, and a second dimension
6 of the collection comprising a spectral dimension, and a processor for deriving a frame
7 from a plurality of two-dimensional collections.

1 28. (Withdrawn) The system of claim 26 wherein the optical fibers in the first and
2 second bundles each have terminating ends arranged in a fiber assembly element fitted to
3 an underside of the platen.

1 29. (Withdrawn) The system of claim 28 wherein the terminating ends of the fibers
2 are arranged in an arrangement in which terminating ends of fibers in the first bundle
3 form first and second rows, and the terminating ends of fibers in the second bundle form
4 a third row placed between the first and second rows.

1 30. (Currently amended) A system for imaging a substrate during CMP, comprising:
2 a carrier holding a substrate, the substrate having a pad-contacting surface;
3 a rotating platen holding a polishing pad;
4 a frame for operatively disposing the rotating platen relative to the carrier; and
5 an image processing subsystem for capturing, from light reflected from the pad-
6 contacting surface and transmitted through one or more optically transparent elements in
7 the platen and/or polishing pad, data points representative of at least a portion of the pad-
8 contacting surface of the substrate during traversal of the opening and/or optically
9 transparent elements, and deriving ~~therefrom~~ from the data points one or more one-

Attorney Docket No. FILM.P008

10 dimensional reflectance images of a portion of a substrate, where data point spacing is
11 determined by an array of data collection locations disposed substantially non-parallel to
12 the direction of substrate motion, wherein the reflectance images comprise an optical
13 representation of the portion of the substrate.

1 31. (Original) The system of claim 30 where the data points used for deriving the
2 one or more images are substantially contiguous.

1 32. (Original) The system of claim 31 where the data points used for deriving the
2 one or more images are substantially non-contiguous.

1 33. (Previously presented) The system of claim 30 where the one or more
2 images are spectral images.

1 34. (Original) The system of claim 30 where the image processing subsystem
2 aggregates the one-dimensional images to form a two-dimensional image of the substrate,
3 and the two-dimensional image provides information about the substrate useful for
4 subsequent chemical-mechanical processing of the substrate.

1 35. (Original) The system of claim 34 where the image processing subsystem
2 forms one or more two-dimensional images of at least a portion of the substrate.

1 36. (Original) The system of claim 35 where the data points used for deriving the
2 one or more images are substantially contiguous.

1 37. (Original) The system of claim 35 where the points used for deriving the one
2 or more images are substantially non-contiguous.

1 38. (Previously presented) The system of claim 35 where the one or more two-
2 dimensional images comprise spectral images.

Attorney Docket No. FILM.P008

1 39. (Currently amended) A method for polishing a semiconductor substrate,
2 comprising:

3 acquiring one or more two-dimensional images of the substrate during CMP,
4 wherein the images comprise an optical representation of at least a portion of the
5 substrate; and

6 deriving ~~therefrom~~ from the images information about the substrate useful for
7 subsequent chemical-mechanical processing of the substrate.

1 40. (Original) The method of claim 39 wherein the derived information
2 comprises frame data suitable for reproducing the one or more two-dimensional images.

1 41. (Original) The method of claim 39 wherein each two dimensional image
2 comprises a plurality of one-dimensional images, each one-dimensional image reflected
3 from a different portion of the substrate.

1 42. (Original) The method of claim 39 wherein the one or more two-dimensional
2 images comprise spectral images.

1 43. (Currently amended) A method of imaging a substrate comprising:
2 holding a substrate having a pad-contacting surface;
3 holding a polishing pad with a rotating platen including one or more optically
4 transparent elements;
5 operatively disposing the rotating platen relative to the pad-contacting surface,
6 such that the pad-contacting surface contacts the polishing pad, and substantially
7 completely traverses the one or more optically transparent elements within a rotation of
8 the rotating platen;
9 capturing, from light reflected from the pad-contacting surface and transmitted
10 through the one or more optically transparent elements, a plurality of one-dimensional
11 images representative of at least a portion of the pad-contacting surface during traversal
12 of the pad-contacting surface past the optically transparent elements, wherein the images
13 comprise an optical representation of at least a portion of the substrate; and

Attorney Docket No. FILM.P008

14 deriving ~~therefrom~~ from the images a frame comprising frame data useful for
15 subsequent chemical-mechanical processing of the substrate.

1 Claim 44 (canceled).

1 45. (Previously presented) The method of claim 43 wherein the capturing
2 comprises:
3 carrying light from a light source to the optically transparent elements in the
4 platen;
5 carrying light reflected from the pad-contacting surface to a wavelength
6 dispersive element; and
7 dissecting spatial components of the one-dimensional images into their respective
8 wavelength components.

1 46. (Currently amended) The method of claim ~~44~~ 45 wherein the capturing further
2 comprises:
3 receiving, at a two-dimensional imager having a spatial dimension and a spectral
4 dimension, dissected light from the wavelength dispersive element; and
5 providing a two-dimensional collection of data for each of the one-dimensional
6 images, a first dimension of the collection comprising a spatial dimension, and a second
7 dimension of the collection comprising a spectral dimension.

1 47. (Previously presented) The method of claim 46 wherein the deriving
2 comprises deriving a frame from a plurality of the two-dimensional collections.

1 48. (Currently amended) A method for acquiring a two-dimensional image of a
2 substrate during CMP, comprising:
3 holding a substrate, the substrate having a pad-contacting surface and a maximum
4 planar dimension;
5 holding a polishing pad with a rotating platen, the platen having a radius and
6 including a slit having a length disposed substantially along the radius of the platen and

Attorney Docket No. FILM.P008

7 equal to or exceeding the maximum planar dimension of the substrate, the platen also
8 including an optically transparent element located at about the slit;
9 operatively disposing the rotating platen relative to the pad-contacting surface,
10 such that the pad-contacting surface of the substrate contacts the polishing pad, and
11 substantially completely traverses the slit within a rotation of the platen;
12 capturing, from light reflected from the pad-contacting surface and transmitted
13 through the optically transparent element, a plurality of one-dimensional images
14 representative of the substantial entirety of the pad-contacting surface of the substrate
15 during traversal of the pad-contacting surface past the slit, wherein the images comprise
16 an optical representation of at least a portion of the substrate; and
17 deriving therefrom from the images a frame comprising frame data providing
18 information about the substrate useful for subsequent chemical-mechanical processing of
19 the substrate.

1 49. (Previously presented) The method of claim 48 wherein the capturing
2 comprises:
3 carrying light from a light source to the slit in the platen;
4 carrying light reflected from the pad-contacting surface to a wavelength
5 dispersive element; and
6 dissecting spatial components of the one-dimensional images into their respective
7 wavelength components.

1 50. (Previously presented) The method of claim 49 wherein the capturing
2 further comprises:
3 receiving, at a two-dimensional imager having a spatial dimension and a spectral
4 dimension, dissected light from the wavelength dispersive element; and
5 providing a two-dimensional collection of data for each of the one-dimensional
6 images, a first dimension of the collection comprising a spatial dimension, and a second
7 dimension of the collection comprising a spectral dimension.

Attorney Docket No. FILM.P008

- 1 51. (Previously presented) The method of claim 50 wherein the deriving
- 2 comprises deriving a frame from a plurality of the two-dimensional collections.